

A Gentle Introduction to SAS/Graph® Software

Ben Cochran, The Bedford Group, Raleigh, NC

Abstract:

The power and flexibility of SAS/GRAPH software enables the user to produce high quality graphs, charts, and maps. With all this strength and flexibility, the new user is sometimes overwhelmed and discouraged from using these powerful tools. However, learning how to use the tools of SAS/GRAPH can be a pleasant experience.

This paper introduces several ways to generate graphical representations of your data. Starting with the importance of understanding their data, users are lead in a step by step process that ends with the generation of high quality plots and graphs. Let us begin.

Step 1: Understanding Your Data. Is some data more appropriate for generating graphical reports than other data? What data is most appropriate for plots and graphs? The first data set to be examined is the SASUSER.RETAIL table.


	Retail sales in millions of \$	date
1	220	1995Q1
2	257	1995Q2
3	258	1995Q3
4	295	1995Q4
5	247	1996Q1
6	292	1996Q2
7	286	1996Q3
8	323	1996Q4
9	284	1997Q1
10	307	1997Q2

A quick look at the first ten rows reveals only 2 columns or variables: SALES, and DATE. The SALES variable has a descriptive label associated with it. Both variables are numeric. One contains monetary values, while the other contains dates. They are both what we would call continuous numeric, in that their values could plotted on a number line. This data set is perfect for 'plotting'.

Step 2: Generating Plots From Your Data. With SAS/GRAPH you can use the GPLOT procedure to plot one variable against another. In this case, we are going to plot 'money' over 'time'. When you have a variable that represents some component of time, it is usually plotted on the horizontal axis, while the 'other' variable is plotted on the vertical axis. It is very easy to tell the SAS system to draw this kind of plot by using the following code:

```
proc gplot data=sasuser.retail;  
  plot sales * date;  
run;
```

The first statement invokes the GPLOT procedure on the SASUSER.RETAIL data set. The first variable mentioned on the PLOT statement is plotted against the vertical axis, while the second variable is plotted against the horizontal axis. This simple code produces the following plot:



This plot is fairly descriptive and you can definitely see the trend throughout time. It's a good trend for this particular organization. However, the plot is somewhat plain. We can enhance the plot by using several of the options available through the PLOT procedure. Let's enhance this plot by: defining a plot symbol,

joining the symbols by straight line segments, and selecting a color. To do this, we will need to use the SYMBOL statement.


The SYMBOL statement allows you to specify the several options at one time that can enhance your plot. Selected options are:

- V or VALUE : specifies the plot symbol
- I : specifies the interpolation method
- CI : specifies the color of the interpolation method
- CV : specifies the color of the plotting symbol
- W or WIDTH : specifies the line thickness.

Next, lets enhance the plot by using the SYMBOL and LABEL statements.

```
proc gplot data = sasuser.retail ;
  plot sales * date ;
  symbol v = triangle i = j ci=red
        w = 5 ;
  label sales = 'Sales';
run;
```

The above SYMBOL statement draws a thick red line through triangles. The LABEL statement shortens the previously defined label to just 5 characters. The output looks like this:




The next step is to enhance the plot by doing the following:

- drawing a reference line
- drawing a green linear regression line

To do this, we will modify the SYMBOL statement as well as use some PLOT statement options. Specifically, we will use the VREF option to draw reference line that references the VERTICAL axis where the value is 500. The LVREF option will be used to make the reference line a solid one. And the CVREF option will be used to make the reference line red.

```
proc gplot data = sasuser.retail ;
  plot sales * date / vref = 500
                    cvref=red lvref=1;
  symbol v = triangle i = rl
        ci = green w = 5 ;
  label sales = 'Sales';
run; quit;
```

The results are shown below:



Other PLOT enhancements will be shown during the presentation of this paper.

Step 3: Generating Bar Charts. You can use SAS/GRAPH to generate fairly simple bar charts. We will do this initially, then go through a series of steps to enhance the output. To generate BAR CHARTS, you use the GCHART procedure.

With the GCHART procedure, you can not only generate BAR CHARTS, but you can also draw PIE and BLOCK charts as well. First, lets take a look at the data.

A modified version of the SASHELP.MDV data set will be used for the PROC GCHART examples. The first ten rows of the data are shown below:

Obs	CODE	COUNTRY	TYPE	CITY
1	NEXT DAY	AUSTRALIA	MD11	ACTON
2	NEXT DAY	AUSTRALIA	DC10	ACTON
3	SECOND DAY	AUSTRALIA	A300	ACTON
4	THIRD DAY	AUSTRALIA	MD11	MELBOURNE
5	SECOND DAY	AUSTRALIA	DC10	MELBOURNE
6	NEXT DAY	AUSTRALIA	747	MELBOURNE
7	SECOND DAY	AUSTRALIA	A300	MELBOURNE
8	NEXT DAY	AUSTRALIA	777	MELBOURNE
9	NEXT WEEK	CANADA	MD11	MONTREAL
10	SECOND DAY	CANADA	DC10	MONTREAL

sales2002	sales2001	sales2000	sales1999
1660.57	1500.24	523.24	288.24
874.62	804.24	523.24	499.24
1340.82	1308.24	523.24	198.24
1876.61	1596.00	1170.00	529.00
1320.58	1178.29	251.29	628.71
1237.36	1144.29	251.29	149.71
1318.61	1106.29	251.29	640.71
1077.62	954.29	251.29	418.71
309.77	268.00	1120.00	948.00
1738.20	1522.00	834.00	121.00

When using the GCHART procedure, you need to specify three things. First, you specify the physical form of the chart. Next, you need to identify the CHART variable as well as the ANALYSIS variable.

The CHART variable determines how many BARS or SLICES (for PIE charts). Usually, you will get one bar (or slice) for each value of the CHART variable. CHART variables are usually character and have values that are discrete and categorical.


The ANALYSIS variable determines the height (or length) of the bars, or the size of the slice. These variables are used for calculating statistics and are always numeric.

To begin with, let's draw a simple BAR CHART. The VP of sales wants to know how much money was made in 2002. So, as a first attempt to find out, the following program was written:

```
proc gchart data = sasuser.mdv2002;
  vbar sales2002;
run;
```

First, a few things need to be pointed out. The VBAR statement determines the physical form of the chart. A vertical bar chart will be generated from this code. Next, SALES2002 is


the CHART variable. Does it have discrete and categorical values? What will determine the height of each bar? Let's look at the output.



Is this what we expected to see? In this case, a numeric charting variable was used. If bars were drawn from each unique value, there would be a lot of bars. What the GCHART procedure did was to automatically calculate the intervals and identify them as MIDPOINTS for SALES2002. This is not usually what we expect to see. So, let's try this again with a different CHART variable.

```
proc gchart data = sasuser.mdv2002;
  vbar country;
run;
```

The variable COUNTRY does have values that are discrete and categorical. What will determine the height of each bar? Let's look at the output.




As you can tell from the output, the height of the bars is determined by a FREQUENCY count. In other words, there were 8 observations in this data set that had AUSTRALIA as the value for COUNTRY, there were 12 observations in this data set that had CANADA as its value for COUNTRY. So, FREQUENCY is the default statistic.

Lets redraw the graph, only this time lets let the height of the bar reflect the total sales for a specific year.

```
proc gchart data = sasuser.mdv2002;
  vbar country /
  sumvar = sales2002;
  title 'Report on 2002 Sales';
run;
```

By using the SUMVAR= option, we are telling the GCHART procedure that we want the height of each bar to be the SUM of SALES2002. Also, we are adding a title to the output.




Lets enhance the output further by doing the following:

- Order the bars by using a descending option on the VBAR statement.
- Make the bars represent the AVERAGE sales (instead of TOTAL sales)
- Place the AVERAGE sales value on the 'top' of each bar.

Use the following code to accomplish these enhancements.

```
proc gchart data = sasuser.mdv2002;
  vbar country / sumvar = sales2002
  type = mean mean
  descending;
  title 'Report on 2002 Sales';
run;
```

The TYPE= option specifies the MEAN statistic. The second 'MEAN' indicates you want the MEAN statistic to be displayed above each bar. The DESCENDING keyword tells the GCHART procedure to display the bars in descending height. The output is shown below:




Its easy to change the physical form of the chart. Change the VBAR statement to HBAR. Since we do not want to draw a chart on the entire data, we will use a WHERE statement to subset the data. Other enhancements will be explained after we examine the code.

```
proc gchart data = sasuser.mdv2002;
  hbar code /
  type = mean
  group = country
  sumvar = sales2002;
  patternid = midpoint;
  title c=blue f=zapf
  '2002 Sales to Japan and Canada';
  where country in('JAPAN',
  'CANADA');
run;
```

You will notice the use of the following options:

- GROUP= to group bars,
- PATTERNID=MIDPOINT to give each bar a different color,
- TITLE statement options to control the color and font of the title text.



Other enhancements will be shown when this paper is presented.

The author can be reached at:

Ben Cochran
The Bedford Group
3216 Bedford Avenue
Raleigh, NC 27607
(919) 831-1191

bedfordgroup@nc.rr.com
www.bedford-group.com



Conclusion

There are a number of ways to generate graphic output with the SAS system. Methods other than SAS/GRAPH may be easier, but none has near the power and control found in the SAS/GRAPH syntax. With its dozens of options and statements, a user can customize their graphic output to create exactly what they want. For more information on SAS/GRAPH, see the documentation offered by SAS Institute.

Go to WWW.SAS.COM and select Services, then Publications.